

LIBERTY SERIES • ROLL CAGE DESIGN

COLD WATER ► GAS POWERED ► BELT DRIVE

- **Rugged Roll Cage Design**
- **Belt-Drive Kärcher Pump**
- **Gas or Diesel Engine with Electric Start**
- **Cleaning Power Up to 5000 PSI**

These electric-start cold water pressure washers with their unique roll cage design are the workhorses of Kärcher's cold water line up, offering cleaning power of up to 5000 PSI. Besides the rugged roll cage made of 1/4" steel, these units are protected by an all-weather powder coat finish and are powered by reliable Honda or Lombardini engines. They also feature tri-plunger oil bath Kärcher pumps, 13-inch tubed pneumatic tires, and an extra rugged belt-drive assembly with notched V-belts and cast iron pulleys. All models are ETL safety certified.

Rugged roll cage and chassis made of 1/4-inch steel and powder coated with an epoxy finish for all-weather protection

Heavy-duty lifting beam for ease in loading and transporting

Safety thermal pump saver valve protects against hot-water damage by venting recirculated water

Five conveniently mounted, quick-couple spray nozzles for varying fan spray

Reliable electric-start, gas-powered Honda or diesel-powered Lombardini engines with two-year warranty; low-oil alert and silent-tone muffler

Inlet strainer protects pump from debris in the water source

Totally enclosed, OSHA-compliant, high-impact polyethylene belt guard and easy-to-adjust belt tension device

Warning and operating instructions in three languages for owner liability protection

Industrial-grade, tri-plunger, oil-bath Kärcher high pressure pump with forged brass head and ceramic pistons



Notched V-belts and cast-iron pulleys reduce belt slippage and provide longer pump life

ETL certified to the rigid UL-1776 safety standards

Insulated, high-pressure trigger gun for hours of fatigue-free cleaning



13" tubed pneumatic tires with steel rims for easy maneuvering on all terrains and to absorb vibration

50' durable wire braid hose rated for 3000 or 5000 PSI; with hose guard for burst protection



Easy-to-attach downstream detergent injector with brass soap nozzle

Insulated plated steel wand with quick-couple connectors for easy attachment of high-pressure nozzles

Optional hose reel available

DISTRIBUTED BY:

Model	Order No.	GPM	PSI	Engine	HP	Fuel	Pump	Ship Wt
HD 4.0/50 PB Cage	1.575-200.0	4.0	5000	Honda	20	Gasoline	Kärcher KX	420 lbs
HD 4.5/50 PB Cage	1.575-201.0	4.5	5000	Honda	24	Gasoline	Kärcher KX	425 lbs
HD 3.4/30 DB Cage	1.575-202.0	3.4	3000	Lombardini	10	Diesel	Kärcher KM	430 lbs

Dimensions: 46"L x 30"W x 36"H