

LIBERTY SERIES

HOT WATER ► ELECTRIC POWERED ► DIESEL HEATED ► ROLL CAGE

- **Rugged roll cage construction with tubed pneumatic tires**
- **Kärcher direct-drive crankcase-style pump**
- **1/2" Schedule 80 heating coil with stainless steel wrap**
- **Industrial electric motor**
- **Variable pressure wand**

Water-resistant control box with burner on/off switch, adjustable thermostat and hour meter

Kärcher's tri-plunger crankcase-style pump with forged brass pump head and ceramic pistons is protected by a 5-year warranty



Four conveniently mounted, quick-couple spray nozzles for varying fan spray

Easy-to-attach downstream detergent injector with brass soap nozzle

Burner is supplied by a 6-gallon polyethylene fuel tank for hours of uninterrupted use

Tri-lingual operating instructions for owner liability protection

36 ft. electrical cord includes ground-fault circuit interrupter for maximum operator safety

Fuel filter/water separator ensures pure fuel supply

120V 1725 RPM or 230V 3450 RPM industrial-grade Baldor motors provide reliable power to the pump

Built on a rugged 1 1/4" powder coated steel frame, these compact electric roll cage models are designed for rugged terrains like construction sites, farms and factories where electricity is available. The three models deliver hot water cleaning of up to 2000 PSI using 120V or 230V 1ph. Each features a Kärcher direct-drive crankcase-style pump with 5-year warranty, industrial-grade Baldor motor, 1/2" Schedule 80 heating coil with stainless steel wrap, pneumatic wheels and North American style accessories, including quick-connect nozzles and an insulated variable spray wand. All are certified to UL and CSA standards.



50 ft. of durable, wire braid hose rated for 3000 PSI and with hose guard for burst protection

Insulated trigger gun for hours of fatigue-free cleaning

Insulated, variable pressure wand with quick-couple connectors for easy attachment of high-pressure nozzles

ETL certified to UL and CSA safety standards

Compact 1 1/4" powder-coated steel roll-cage frame protects machine components and is highly maneuverable

Insulated Schedule 80 hot water coil made of 1/2-inch steel pipe and cold rolled for long life; comes standard with stainless steel coil wrap and 5-year warranty

Rupture disk provides added safety by protecting against excessive pressure buildup

High-efficiency burner with transformer for years of reliable and affordable operation

Thermal pump saver valve protects against hot-water damage by venting recirculated water

Available Option: Hose reel



Four tubed pneumatic tires absorb vibration and provide added portability

DISTRIBUTED BY:

Model	Order No.	GPM	PSI	HP	Electrical	Amps	Drive	Pump	Ship Wt
HDS 2.0/10 Ed Cage	1.575-511.0	2.0	1000	1.5	120V/1ph	15	Direct	Kärcher KE	480 lbs
HDS 1.9/15 Ed Cage	1.575-512.0	1.9	1500	2	120V/1ph	20	Direct	Kärcher KE	480 lbs
HDS 3.5/20 Ea Cage	1.575-513.0	3.5	2000	5	230V/1ph	22	Direct	Kärcher KE	500 lbs

Dimensions: 39"L x 27"W x 44"H