

LIBERTY SERIES

HOT WATER ► GAS POWERED ► DIRECT DRIVE

- **Totally Self-Contained, Portable**
- **Direct-Drive Crankcase Pump**
- **Schedule 80 Heating Coil**
- **Honda or Robin Engines**
- **Up to 3.5 GPM, 3500 PSI**

These portable, gas-powered, diesel-heated hot water pressure washers are loaded with heavy-duty components and a rugged steel chassis. Their compact frame design along with tubed pneumatic tires provide easy maneuvering in any terrain. Each unit is ETL certified to UL and CSA safety standards and has a Schedule 80 steel heating coil with stainless steel wrap and 5-year warranty. Extra-compact 6 and 7 HP models are available. ►



Industrial-grade Honda and Robin engines with two-year warranty; two models with electric-start standard

Rugged 1¼" steel tube frame with epoxy, powder coat finish for all-weather protection

Power platform cushioned on 4 vibration isolators for smoother operation and long-life protection to frame and components

Four conveniently mounted, quick-couple spray nozzles for varying fan spray

Safety relief valve attached to discharge side for protection against excessive pressure build up

13-Inch tubed pneumatic tires for easy handling on all terrains

Rust-free, 6-gallon polyethylene diesel fuel tank for hours of generating hot water without interruption

Industrial-grade tri-plunger oil-bath direct-drive Kärcher pump with 5-year warranty



Insulated Schedule 80 hot water coil is made of 1/2-inch steel pipe and cold rolled; comes standard with stainless steel coil wrap and 5-year warranty

Insulated trigger gun for hours of fatigue-free cleaning

Water resistant control box with burner on/off switch, adjustable thermostat and hour meter

Insulated, dual-lance variable pressure wand with quick-couple connectors for easy attachment of high-pressure spray nozzles

50 ft. of durable, wire braid hose rated for 3000 or 4500 PSI; with hose guard for burst protection

Thermal pump saver valve protects against hot-water damage by venting recirculated water

Tri-lingual operating instructions for owner liability protection

High-efficiency burner with transformer for years of reliable and affordable operation

Available Options: Hose reel and steam combination

ETL certified to UL and CSA safety standards

Easy-to-attach downstream detergent injection with quick couplers

DISTRIBUTED BY:

Model	Order No.	GPM	PSI	Drive	Engine	Start	Burner	Pump	Ship Wt
HDS 2.5/20 P Cage*	1.575-554.0	2.5	2000	Direct	Robin 6	Recoil	12V DC	Kärcher KG	390 lbs
HDS 2.8/25 P Cage*	1.575-555.0	2.8	2500	Direct	Robin 7	Recoil	12V DC	Kärcher KG	410 lbs
HDS 2.6/30 P Cage*	1.575-550.0	2.6	3000	Direct	Honda 9	Recoil	12V DC	Kärcher KG	530 lbs
HDS 3.5/30 P Cage*	1.575-551.0	3.5	3000	Direct	Honda 11	Recoil	12V DC	Kärcher KS	545 lbs
HDS 3.5/30 Pe Cage	1.575-552.0	3.5	3000	Direct	Honda 11E	Electric	12V DC	Kärcher KS	560 lbs
HDS 3.5/35 Pe Cage	1.575-553.0	3.5	3500	Direct	Honda 13E	Electric	12V DC	Kärcher KS	570 lbs

Dimensions: 6-7 HP: 39"L x 28"W x 42"H; 9-13 HP: 46"L x 28"W x 44"H * No Battery Needed