



## SelectSpot™

- A clear recovery tank with 2 dumping ports allows for ease of cleaning
- Exhaust air is filtered for maintaining indoor air quality
- Optional cart is designed with a tray and holds cleaning accessories

## Rainmaker® H and C

- Both models have a 14 gallon solution tank and 100 psi
- Features onboard storage of a floor tool and storage compartments
- Rainmaker H features instant heat to 212° at the wand tip and a circuit locator



## Xtrac™



- CRI Seal of Approval
- 12" carpet extractor with 5 gallon solution tank
- Scrub brush can be removed and installed without use of tools
- Optional quick connect for spotting
- Single Spray Jet technology for even water coverage, no clogging, low gpm
- Compact folding handle and built in handgrips make Xtrac easy to transport

## Klenzor® 16 and 18 MPH



- CRI Seal of Approval
- 16" and 18" cleaning paths allow for high productivity
- A utility bag is attached to hold pre-spray or spotting solution
- Brush assisted, reducing operator fatigue
- Adjustable handle for various height operators
- Durable 7 gallon (Klenzor 16) and 11 gallon (Klenzor 18 MPH) solution tanks
- Durable 5 gallon (Klenzor 16) and 8 gallon (Klenzor 18 MPH) recovery tanks
- The vacuum shoe design means better extraction for higher recovery and quick dry times
- Tools-free brush and vacuum shoe removal makes maintenance quick and easy
- Single brass fan spray jet provides an even spray without streaking, clogging or over-wetting
- Optional tools-free hard floor cleaning attachment available



<b>Models:</b>	<b>SelectSpot™</b>
<b>Vacuum Motor:</b>	1 hp, 786 watt, 2-stage
<b>Solution Pump:</b>	38 p.s.i. (2.6 bar) output
<b>Solution Hose:</b>	9 ft x 0.25 in (2.7 m x 6.4 mm) nylon braided PVC
<b>Solution Tank:</b>	2 gal (7.6 L)
<b>Recovery Tank:</b>	2 gal (7.6 L) w/2 in (5 cm) threaded drain cap
<b>Recovery Hose:</b>	8 ft x 1 in (2.4 m x 2.5 cm) wire-wound PVC
<b>Hand Tool:</b>	Clear plastic, 3.5 in (8.9 cm) wide with stainless steel handle
<b>Exhaust Filter:</b>	Filtrete™ by 3M®, 90% efficient on 0.5 microns @ 100 feet/min.
<b>Sound Level:</b>	73 dB A average @ 3 ft (0.9 m)
<b>Construction:</b>	Rotational molded polyethylene
<b>Net Weight:</b>	25.75 lb (11.7 kg) w/hose and cord, 20.5 lb (9.3 kg) machine only
<b>Shipping Weight:</b>	35 lb (15.9 kg) w/hose and cord

<b>Models:</b>	<b>Rainmaker® H</b>	<b>Rainmaker® C</b>
<b>Solution Pump:</b>	100 psi	100 psi
<b>Solution Tank Capacity:</b>	14 gallons (53 L)	14 gallons (53 L)
<b>Recovery Tank Capacity:</b>	12 gallons (45 L)	12 gallons (45 L)
<b>Vacuum Motors:</b>	2 - 2 stage	2 - 2 stage
<b>Built-in Heater:</b>	Yes	No
<b>Waterlift:</b>	150 in (381 cm)	150 in (381 cm)
<b>Air Flow:</b>	100 cfm	100 cfm
<b>Solution Hose Length:</b>	15 ft (4.5 m)	15 ft (4.5 m)
<b>Recovery Hose Length:</b>	15 ft (4.5 m)	15 ft (4.5 m)
<b>Rear Wheels:</b>	10 in (25 cm)	10 in (25 cm)
<b>Front Castors:</b>	4 in (10 cm)	4 in (10 cm)
<b>Power Cord:</b>	2 - 25 ft, yellow	1 - 25 ft, yellow
<b>Length:</b>	36 in (91 cm)	36 in (91 cm)
<b>Width:</b>	17 in (43 cm)	17 in (43 cm)
<b>Height:</b>	38 in (96 cm)	38 in (96 cm)
<b>Machine Weight:</b>	83 lb (37 kg)	78 lb (35 kg)

<b>Models:</b>	<b>Xtrac™</b>
<b>Cleaning Path:</b>	12 in
<b>Solution Tank:</b>	5 gal
<b>Recovery Tank:</b>	4 gal
<b>Vacuum Motor:</b>	1.2 hp, 2 stage
<b>Brush Motor:</b>	1/4 hp
<b>Waterlift:</b>	85 in (216 cm)
<b>Vacuum Shoe:</b>	12 in (30.5 cm)
<b>Flow Rate:</b>	0.43 gal @ 60 psi
<b>Power Cable:</b>	25 ft Safety Yellow
<b>Weight:</b>	68 lb

<b>Models:</b>	<b>Klenzor® 16</b>	<b>Klenzor® 18 MPH</b>
<b>Cleaning Path:</b>	16 in (40.6 cm)	18 in (45.7 cm)
<b>Solution Tank:</b>	7 gal (26.5 L)	11 gal (41.6 L)
<b>Recovery Tank:</b>	5 gal (19 L)	8 gal (30.2 L)
<b>Pump:</b>	60 psi	60 psi
<b>Flow Rate:</b>	0.7 gpm	0.7 gpm
<b>Vacuum Motor:</b>	1.5 hp, 3 stage	1.5 hp, 3 stage
<b>Waterlift:</b>	117 in (297 cm)	117 in (297 cm)
<b>Brush Motor:</b>	1/3 hp	1/3 hp
<b>Brush Size/Cleaning Path:</b>	16 in (40.6 cm)	18 in (45.7 cm)
<b>Vacuum Shoe Size:</b>	18 in (45.7 cm)	20 in (50.8 cm)
<b>Power Cable:</b>	50 ft (15 m)	50 ft (15 m)
<b>Min Machine Length:</b>	29.5 in (79 cm)	28 in (71 cm)
<b>Machine Width:</b>	20 in (51 cm)	24 in (61 cm)
<b>Tank Height:</b>	29.5 in (75 cm)	31.75 in (81 cm)

**KENT**  
Simple. Clean.

14600 21st Avenue North  
Plymouth, Minnesota 55447-3408  
www.kenturoclean.com  
Phone 800-545-4372  
Fax 866-261-4779

240 Superior Boulevard  
Mississauga, Ontario, Canada L5T 2L2  
www.kenturoclean.com  
Phone 905-564-1149 or 800-668-8400  
Fax 905-564-1030 or 800-263-5111

