



IMPRESSIONS™

Brilliant Gloss / Ultra Wear Floor Finish

DESCRIPTION

A proprietary blend of synergistic polymers provide uncompromised benefits of immediate wet look gloss and outstanding wearability. Sophisticated integrated components allow for rapid drying, enhanced leveling and superior repairability. This versatile product can be used in many varied environments and maintained with both high & low speed equipment.

PRODUCT FEATURES / BENEFITS

- Very hard wear surface / Extremely scuff resistant
- Enhanced leveling; repairs easily / Usable by any personnel in many applications
- Super brilliant gloss / Maximizes appearance & user appeal
- Fast drying / Allows faster re-coating and less waiting
- Pure thermoplastic polymers / Very responsive to multi-speed polishing

DIRECTIONS FOR USE

A proprietary blend of synergistic polymers provide uncompromised benefits of immediate wet look gloss and outstanding wearability. Sophisticated integrated components allow for rapid drying, enhanced leveling and superior repairability. This versatile product can be used in many varied environments and maintained with both high & low speed equipment.

Maintenance: Maintain in the conventional manner by cleaning with a treated yarn dust mop to remove surface dirt daily. Damp mop or clean with an automatic scrubber as required, using an approved neutral cleaner at the specified dilution. Spray buffing to remove embedded soils is recommended. Worn areas, or the entire floor, may be re-coated as required to maintain a uniform high gloss. When stripping becomes necessary use an approved stripper for detergent resistant finishes.

Floor Preparation: Strip floor of old finish and wax, paying particular attention to baseboards, corners, under furniture, and built up areas. Rinse thoroughly with clean water and allow to completely dry. Application: If desired one or two coats of an approved sealer may be used, prior to finish application. Using a clean mop or applicator apply a thin uniform coat of finish. Allow to dry for a minimum of 20 minutes after each coat. Do not apply

more than 4 coats in a 24 hour period. Floor should be thoroughly dry before traffic is allowed in area. Spray Buff: To restore original luster, polish with an approved spray buff compound or laminator.

High Speed Burnishing: This is an ideal product for use with high speed polishing or burnishing machines of 1000 rpm or higher. The floor should first be damp mopped with a suitable neutral cleaner and allowed to dry. The surface may then, as desired, be dry burnished with a high speed white or tan buffing pad, or using the same equipment, be spray buffed using an approved product. An alternate method, for insuring a long lasting durable surface, would be to apply an approved mop-on restorer or laminator, allow to dry and then to follow the dry buffing procedure. Floor finish can also be polished by auto scrub method.

Maintenance: Maintain in the conventional manner by cleaning with a treated yarn dust mop to remove surface dirt daily. Damp mop or clean with an automatic scrubber as required, using an approved neutral cleaner at the specified dilution. Spray buffing to remove embedded soils is recommended. Worn areas, or the entire floor, may be re-coated as required to maintain a uniform high gloss. When stripping becomes necessary use an approved stripper for detergent resistant finishes.

SPECIFICATIONS

Type	Pure acrylic polymers
Solids (%)	21 ± 0.5
pH	9.0 ± 0.5
Coverage (sq. ft./gal)	2500
Drying Time (minutes)	20-30
Color	White, opaque liquid
Odor	Acrylic
Film Appearance	Clear
Powdering	None
Flash Point	None
Freeze thaw stable	Yes (3 Freeze Thaw Cycles)

Detergent Resistant	Yes
Multi-Speed Buffing	Yes
Leveling	Excellent
Black Mark Resistant	Superior
Scuff Resistance	Superior
Soil Resistance	Superior
Durability	Excellent
Recoatability	Excellent
Removability	Excellent
Immediate Wet Look Gloss	Outstanding
Slip Resistant	Yes
Shelf Life	1 year minimum in original unopened container

SAFETY INFORMATION

CAUTION: HARMFUL IF SWALLOWED. MAY CAUSE SKIN AND EYE IRRITATION. KEEP OUT OF REACH OF CHILDREN. Avoid contact with eyes. Do not ingest. If ingested may cause severe gastric distress and blockage.

FIRST AID: For Eyes: Flush thoroughly with water for at least fifteen minutes. If irritation persists seek medical attention. **For**

Skin: Wash thoroughly with soap and water. If irritation persists seek medical attention. **If ingested:** Do not induce vomiting. Give large quantities of water. Seek medical attention. Never give anything by mouth to an unconscious person. KEEP FROM FREEZING

FOR PROFESSIONAL USE ONLY



FLOOR CARE



Floor Finish and Finishing Material
As to Slip Resistance Only 18EL

HMIS HAZARD CODE	
1	HEALTH
0	FLAMMABILITY
0	REACTIVITY
0	PERSONAL PROTECTION



401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail:info@nclonline.com