



# ONE COAT 25

## Super High Gloss Floor Finish

### DESCRIPTION

A high gloss — high solids pure thermoplastic floor finish which is extremely durable and can be maintained with conventional or high speed floor care systems. This pure acrylic floor finish is produced in high pressure reactors using proprietary molecularly engineered polymers, the finest high pressure micronized wax emulsion, preservatives, leveling aids, interacted plasticizers and deionized water to offer a premium grade floor finish.

### PRODUCT FEATURES / BENEFITS

- High solids formula / Offers labor and material savings by limiting the number of wear coats which must be applied
- Pure thermoplastic polymers / Responsive to high speed burnishing
- May be used with conventional or high speed floor maintenance systems / Allows versatility and reduced inventory levels of additional products
- Very hard wear surface / Extremely scratch and scuff resistant
- Designed for ease of application / May be applied by any personnel without extensive training

### DIRECTIONS FOR USE

A premium quality high solids floor finish that provides a long lasting diamond bright gloss in one application. Durable, detergent resistant, easy application, nonslip, non-scuff, non-black marking and metal bonded for outstanding wear and appearance with a minimum of maintenance. Recommended for all floors.

Preparation of Floors: Strip floors of all old wax and finish with particular emphasis on built up areas along baseboards and corners. Rinse floor thoroughly with clean water and allow to dry.

**Application of Finish:** For best results seal terrazzo, concrete, cork, wood and porous resilient tile floors before application of finish. Apply a thin uniform coat of finish in the conventional manner. Allow finish to thoroughly dry before allowing traffic on

the floor. One coat will provide outstanding beauty and gloss on all sealed floors. If floor is unsealed or highly porous, a second coat may be required on the initial application.

**Maintenance:** Maintain in the conventional manner by cleaning with a treated yarn dust mop to remove surface dirt daily. Damp mop or clean with an automatic scrubber as required, using an approved neutral cleaner at the specified dilution. Spray buffing to remove embedded soils is recommended.

Worn areas, or the entire floor, may be re-coated as required to maintain a uniform high gloss. When stripping becomes necessary use an approved stripper for detergent resistant finishes.

### SPECIFICATIONS

Type ..... Metal Bonded Integrated Polymer  
 Drying Time (minutes) ..... 30  
 Odor ..... Pleasant  
 Color ..... White, opaque liquid  
 Solids Content (%) ..... 25 ± 0.5  
 pH ..... 8.4 ± 0.2  
 Coverage (sq. ft./gal) ..... 2500  
 Powdering ..... Nil  
 Film Appearance ..... Clear  
 Non-yellowing ..... Yes  
 Flash Point ..... None

Nonslip ..... Yes  
 Freeze thaw stable ..... Yes  
 Detergent Resistant ..... Yes  
 One Coat Gloss ..... Superior  
 Durability ..... Superior  
 Soil Resistance ..... Superior  
 Scuff Resistance ..... Superior  
 Black Mark Resistance ..... Superior  
 Leveling ..... Excellent  
 Recoatability ..... Excellent  
 Removability ..... Excellent  
 Shelf Life ..... 1 year minimum in original unopened container

### SAFETY INFORMATION

**CAUTION: MAY BE HARMFUL IF SWALLOWED. MAY CAUSE SKIN AND EYE IRRITATION.** Avoid contact with eyes. Do not ingest. If ingested may cause severe gastric distress and blockage.

**FIRST AID: For Eyes:** Flush thoroughly with water for at least fifteen minutes. If irritation persists seek medical attention. **For**

**Skin:** Wash thoroughly with soap and water. If irritation persists seek medical attention. **If ingested:** Do not induce vomiting. Give large quantities of water. Seek medical attention. Never give anything by mouth to an unconscious person.

KEEP FROM FREEZING  
FOR PROFESSIONAL USE ONLY



Floor Finish and Finishing Material  
As to Slip Resistance Only 18EL

HMIS HAZARD CODE	
1	HEALTH
0	FLAMMABILITY
0	REACTIVITY
0	PERSONAL PROTECTION



401 N. 10th Street • Philadelphia, PA 19123  
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517  
www.nclonline.com • e-mail:info@nclonline.com