



# WORLD CLASS

## Ultra High Speed Sealer / Finish

### DESCRIPTION

Utilizing Integrated Fusion Polymer (IFP) technology, this revolutionary floor coating offers the perfect balance of deep wet look gloss with extended gloss retention and exceptional film wearability. IFP technology provides a "tightness" or density to the polymer system that is significantly greater than conventional high speed floor finishes. Because of the enhanced gloss retention of this ultra high speed product, daily burnishing is not required to maintain the maximum gloss. One or two burnishings per week in heavy traffic areas is all that is required to maintain a deep, brilliant gloss. This product is the ideal choice for any ultra high speed maintenance program.

### PRODUCT FEATURES / BENEFITS

- Sealer / Finish / Simplifies floor care system
- Immediate deep wet look gloss / Dazzling gloss without burnishing
- Long term gloss retention / Less maintenance needed to keep original lustre
- Utilizes IFP technology / Enhances durability & maximizes resistance to soiling, black heel marks and scuffing
- Enhanced leveling / Easy to use by any service personnel

### DIRECTIONS FOR USE

Integrated fusion polymer technology has led to the creation of a very tough, long lasting sealer/finish with a flexible film offering outstanding buffability by high speed buffing or ultra high speed burnishing. Gives outstanding performance on all types of resilient flooring including vinyl, VAT, and vinyl composition tile, also for terrazzo, asphalt, stone and quarry tile and other hard surface floors.

#### This revolutionary sealer/finish exhibits:

- instant deep wet look
- long term gloss retention
- black mark resistant
- excellent dirt release
- extended restoration cycles
- outstanding leveling
- superior durability
- easy repairability
- user friendly formula

**Floor Preparation:** Strip floor of old finish and wax, paying particular attention to baseboards, corners, under furniture, and built up areas. Rinse thoroughly with clean water and allow to completely dry.

**Application:** Using a clean mop or applicator apply a thin uniform

coat of sealer/finish. Allow to dry for a minimum of 30 minutes after each coat. Do not apply more than 4 coats in a 24 hour period. Floor should be thoroughly dry before traffic is allowed in area.

**High Speed Buffing and Burnishing:** This is an ideal product for use with high speed polishing or burnishing machines of 1000 rpm or higher. Prior to high speed buffing or burnishing the floor surface should be dust or dry mopped. After the floor finish has set for two days damp mopping prior to buffing is also acceptable. When buffing or dry burnishing use a peach or tan buffing pad. Approved mop on restorers or laminators can be used when surface is worn.

**Maintenance:** Maintain in the conventional manner by cleaning with a treated yarn dust mop to remove surface dirt daily. Damp mop or clean with an automatic scrubber as required, using an approved neutral cleaner at the specified dilution. Spray buffing to remove embedded soils is recommended. Worn areas, or the entire floor, may be re-coated as required to maintain a uniform high gloss. When stripping becomes necessary use an approved stripper for detergent resistant finishes.

### SPECIFICATIONS

Type .....	Integrated Fusion Polymer
Color .....	White, opaque liquid
Odor .....	Typical acrylic
Non-Volatile Solids (%).....	22.0 ± 0.5
pH.....	8.4 - 8.8
Drying Time (minutes).....	30
Coverage (sq. ft./gal).....	2,500
Specific Gravity (gr/cc) .....	1.032
Density (lbs/gal) .....	8.597
Slip Resistant .....	Yes

Freeze Thaw Stable .....	Yes (3 cycles)
Detergent Resistant .....	Yes
Leveling .....	Excellent
Black Mark Resistant.....	Excellent
Scuff Resistant .....	Excellent
Resistant to Soiling .....	Excellent
Gloss Retention .....	Excellent
Immediate Wet Look Gloss .....	Outstanding
Shelf Life.....	1 year minimum in original unopened container

### SAFETY INFORMATION

**CAUTION:** HARMFUL IF SWALLOWED. MAY CAUSE SKIN AND EYE IRRITATION. KEEP OUT OF REACH OF CHILDREN. Avoid contact with eyes. Do not ingest. If ingested, may cause severe gastric distress and blockage.

**FIRST AID: For Eyes:** Flush thoroughly with water for at least fifteen minutes. If irritation persists seek medical attention. **For**

**Skin:** Wash thoroughly with soap and water. If irritation persists seek medical attention. **If ingested:** Do not induce vomiting. Give large quantities of water. Seek medical attention. Never give anything by mouth to an unconscious person.

KEEP FROM FREEZING  
FOR PROFESSIONAL USE ONLY



FLOOR CARE



Floor Finish and Finishing Material  
As to Slip Resistance Only 18EL

HMIS HAZARD CODE	
1	HEALTH
0	FLAMMABILITY
0	REACTIVITY
0	PERSONAL PROTECTION



National Chemical Laboratories, Inc.  
World Class Cleaning Solutions®

401 N. 10th Street • Philadelphia, PA 19123  
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517  
www.nclonline.com • e-mail:info@nclonline.com