


Industrial-Duty, Gas/Diesel-Powered Pressure Washer

Belt-Drive, Cage Design for Commercial Applications









Cold Water | Gas or Diesel Powered | Belt Drive



Liberty HD PB/DB Cage

Our roll cage models are the most powerful units in our cold water line, with cleaning power of up to 5000 PSI. Protected by a rugged powder coated roll cage built of 1-1/4" steel, the PB Cage units feature powerful Vanguard, Honda or Kohler engines, tri-plunger oil bath Kärcher pumps, 13-inch tubed pneumatic tires, and an extra rugged belt-drive assembly with notched V belts and cast iron pulleys. All single- and double-axle models are ETL safety certified.



Powerful and durable

- Safety thermal pump saver valve protects against hot-water damage by venting recirculated water.
- Rugged roll cage and chassis made of 1 1/4-inch steel and powder coated with an epoxy finish for all-weather protection.
- Reliable Honda, Vanguard or Lombardini engines with 2-year warranty; low-oil alert and silent-tone muffler.
- Industrial-grade, tri-plunger, oil-bath Kärcher high pressure pump with forged brass head and ceramic pistons; backed by 7-year warranty.
- Notched V-belts and cast-iron pulleys reduce belt slippage and provide longer pump life.
- 50' durable wire-braid hose rated for 3000 or 5000 PSI; with hose guard for burst protection
- Inlet strainer protects pump from debris in the water source.

Smart features

- Five conveniently mounted, quick-couple spray nozzles for varying fan spray.
- Totally enclosed, OSHA-compliant, high-impact polyethylene belt guard and easy-to-adjust belt tension device.
- Insulated, high-pressure trigger gun for hours of fatigue-free cleaning.

Outstanding mobility

- Heavy-duty lifting beam for ease in loading and transporting.
- 13" tubed pneumatic tires with steel rims for easy maneuvering on all terrains and to absorb vibration.



Technical Data and Equipment

HD 3.7/35 PB Cage HD 4.0/40 PB Cage HD 4.0/50 PB Cage* HD 4.5/50 PB Cage* HD 3.4/30 DB Cage*

- Belt-drive
- Rugged steel chassis & roll cage
- Powerful Honda, Vanguard or Kohler engine
- Cleaning power up to 5000 PSI
- Electric start on dual-axle models*
- Industrial belt-drive Kärcher pump with 7-year warranty
- 13" tubed pneumatic tires







Technical Data						
GPM		3.7	4.0	4.0	4.5	3.4
PSI		3500	4000	5000	5000	3000
Engine		Honda GX390	Vanguard 16	Honda GX630	Honda GX660	Kohler KD420
CC		389	479	688	688	404
Start		Recoil	Recoil	Electric	Electric	Electric
Fuel		Gas	Gas	Gas	Gas	Diesel
Pump		Kärcher KM	Kärcher KT	Kärcher KX	Kärcher KX	Kärcher KM
Axles		1	2	2	2	2
Ship Weight	lbs.	350	470	495	500	410
Dimensions (L x W x H)	inches	42 x 26 x 30	42 x 26 x 36			
Order No.		1.575-205.0	1.575-207.0	1.575-200.0	1.575-201.0	1.575-202.0

Options (field installed)

9.801-028.0 EZEE 100' Hose Reel kit, single axle (hose not included)

9.801-029.0 100' Hose Reel kit, 5000 psi, double axle (hose not included)



Your Authorized Kärcher Professional Dealer:

Kärcher Commercial Phone 888-805-9852 Fax 800-248-8409 info@karchercommercial.com www.karchercommercial.com