

Gasoline-powered, direct-drive, pressure washer

Cold water power with handtruck design for commercial applications



Cold Water | Gas Powered | Direct Drive



HD Handtruck Design

This series of commercial-duty, gas-powered cold water pressure washers offers the ideal balance between professional performance and value. Powered by reliable Honda engines, all four models have Kärcher's German-engineered, direct-drive axial pump, rugged steel frame with handtruck design, tubed pneumatic tires and 50' of commercial-duty hose (GX engine model come with a 100 ft. hose reel).



Powerful and durable

- Rugged steel frame and power platform, with easy-to-manuever handtruck design, is painted with a black, wrinkle-coat finish for all- weather protection.
- Reliable Honda engine with two-year warranty, low-oil alert and silent-tone muffler; 9 and 13 HP models have an EZ-start valve for resistance-free pull starting of engine.
- Three-piston, direct-drive Kärcher axial pump with unique swash plate design has fewer moving parts for a highly efficient, smooth and quiet operation; brass cylinder head ensures extra durability and extended life.
- 50' durable wire braid hose rated for 3000 or 4000 PSI.
- Inlet strainer protects pump from debris in the water source.
- Top-mounted 100' hose reel (comes standard only on 9 and 13 HP models) simplifies clean up and reduces risk of high- pressure hose being damaged.

Smart features

- Easy-to-attach downstream detergent injector with brass soap nozzle.
- Five conveniently mounted, quick- couple spray nozzles for varying fan spray.
- Insulated, high-pressure trigger gun for hours of fatigue-free cleaning.

Outstanding mobility

- 10" tubed pneumatic tires for easy maneuvering on all terrains and to absorb vibration; front- mounted rubber feet also absorb vibration and keep the unit from "walking" during operation.
- Upright design for easy, ergonomic transport.

Technical Data and Equipment

HD 2.5/24 P

HD 2.6/26 P

HD 3.1/31 P

HD 4.0/36 P

- Reliable Honda engines
- Kärcher axial pump
- Reinforced upright steel frame
- Unmatched value

- includes 100' hose reel

- includes 100' hose reel

Technical Data

	2.5	2.6	3.1	4.0
GPM	2.5	2.6	3.1	4.0
PSI	2400	2600	3100	3600
Engine	Honda GC160	Honda GC190	Honda GX270	Honda GX390
CC	160	187	270	389
Pump	Axial	Axial	Axial	Axial
Ship Weight lbs.	148	155	166	180
Dimensions (L x W x H) inches	35 x 21 x 24	35 x 21 x 24	24 x 32 x 43	24 x 32 x 43
Order No.	1.575-105.0	1.575-106.0	1.575-107.0	1.575-108.0

Options (field installed)

9.801-253.0	Non-pivoting hose reel, 100' (hose not included)
-------------	--



makes a difference

Your Authorized Kärcher Professional Dealer:

Kärcher Commercial
Phone 888-805-9852
Fax 800-248-8409
info@karchercommercial.com
www.karchercommercial.com