

Portable, Hot Water Power, Pressure Washer

Easy-Handling for Commercial Applications



Hot Water | Gas Powered | Diesel Heated



Liberty HDS P/Pe Cage

These portable gas-powered hot water units are built using heavy-duty components and rugged steel chassis to withstand the most rigorous conditions. Their compact frame design and pneumatic tires provide easy maneuvering in all terrains. Each unit is ETL certified to UL and CSA safety standards and comes with a leak free Schedule 80 heating coil surrounded by a standard stainless steel wrap.

Powerful and durable

- Industrial-grade Honda and Robin engines with two-year warranty; two models with electric-start standard.
- Efficient burner with transformer for years of reliable and affordable operation.
- Industrial-grade, tri-plunger, oil-bath, direct-drive, Kärcher pump with 7-year warranty.
- 50 ft. of durable, wire braid hose rated for 3000 or 4500 PSI; with hose guard for burst protection.
- Heavy-gauge 11/4" steel frame with powder coat finish for all-weather protection.
- Power platform cushioned on 4 vibration isolators for smoother operation and long-life protection to frame and components.
- Insulated Schedule 80 heating coil is made of 1/2-inch steel pipe and cold-rolled; comes standard with stainless steel coil wrap and 5-year warranty.

Smart features

- Four conveniently mounted, quick-couple spray nozzles for varying fan spray.
- Safety relief valve attached to discharge side for protection against excess pressure build up.
- Rust-free, 6-gallon polyethylene diesel fuel tank for hours of operation without interruption.
- Insulated, high-pressure trigger gun for hours of fatigue-free cleaning.
- Water resistant control box with burner on/off switch, adjustable thermostat and hour meter.
- Thermal pump saver valve protects against hot-water damage by venting recirculated water.
- Insulated, dual-lance variable pressure wand with quick-couple connectors for easy attachment of high-pressure spray nozzles.

Technical Data and Equipment

HDS 2.8/25 P Cage

HDS 2.6/30 P Cage

HDS 3.5/30 P Cage

HDS 3.5/30 Pe Cage

HDS 3.5/35 Pe Cage

- Direct-drive tri-plunger pumps
- Stainless steel coil wrap standard
- Rugged frame with powder finish
- Pneumatic tires
- Schedule 80 heating coil
- ETL certified to UL & CSA Standards



Technical Data

GPM	2.7	2.6	3.5	3.5	3.5
PSI	2400	3000	3000	3000	3500
Engine	Subaru EX21	Honda GX270	Honda GX340	Honda GX340	Honda GX390
CC	211	270	389	389	389
Start	Recoil	Recoil	Recoil	Electric	Electric
Pump	Kärcher KG	Kärcher KG	Kärcher KS	Kärcher KS	Kärcher KS
Burner	12V DC	12V DC	12V DC	12V DC	12V DC
Ship Weight lbs.	404	500	550	560	595
Dimensions (L x W x H) inches	39 x 28 x 42	39 x 28 x 42	46 x 28 x 44	46 x 28 x 44	46 x 28 x 44
Order No.	1.575-555.0	1.575-550.0	1.575-551.0	1.575-552.0	1.575-553.0

Options (field installed)

9.801-024.0	100' EZEE hose reel kit (hose not included)
9.804-570.0	100' pivot hose reel kit (hose not included)



makes a difference

Your Authorized Kärcher Professional Dealer:

Kärcher Commercial
Phone 888-805-9852
Fax 800-248-8409
info@karchercommercial.com
www.karchercommercial.com